### INK JET MARKER

## SingleDot - Pia





# A big printer in a small format

- Robust Metal housing and IP65
- Simple Easy to setup and to operate
- Flexible Can print on almost any surface
- Compact Very small size. Easy to fit into your production environment



## SingleDot Pia - Specifications

#### PRINTER FEATURES

- Single nozzle print head.
- Can print dotted line continuous line or pattern;
- Ink throw distance up to 10 cm optimally, longer distance are possible
- Adjustable dotsize
- Nozzle sizes;
   350, 270, 150 & 80 μm
- Can print on almost any surface
- Integrated controller
- USB for setup of printing and firmware upgrade

#### **AREAS OF APPLICATION**

- Ok/Not ok product marking
- · Length marking
- Dots and lines for cutting marks
- Quality grade with different ink colors

49


- Identification
- Nail marking
- Inkjet Pencil

#### **ENVIRONMENT**

- Air supply: 1-10 bar.
- Electrical power supply:
   100-240 V~, 50/60Hz, 0.7A
- Idle mode consumption:
   3 W, 0,03 A
- Protection: IP 65
- Outdoor and indoor use.

### CONNECTIVITY

- INI:
- 2 x PNP/NPN Opto inputs for tachometers and photocell 7 - 30V
- 1 x Analog input O 3O volt
- OUT:
  - 2 x Print head connections
- Connectivity for 3 external potentiometers for adjustment of printing parameters.



Inkit AB
Smidesgatan 5
417 07 Göteborg

Sweden

Email: info@inkit.se
Webb: www.inkit.se

Tel: 46 31 96 66 88



